

Kable Kontrol® Heat Resistant Silicone Jacketed Fiberglass Wire Sleeve

Technical Specifications

Part Number	Inside Diameter	Wall Thickness (mm)	Operating Temperature	Peak Tolerance (for 30 Seconds)	Length	Color	Case Quantity
HTBS-B-025-RD	1/4" (6.35 mm)	1.5 ± 0.50	-76°F to 500°F (-60°C to 260°C)	3002°F (1650°C)	65 Feet	Red	10 Spools
HTBS-B-050-RD	1/2" (12.7 mm)	2 ± 0.50	-76°F to 500°F (-60°C to 260°C)	3002°F (1650°C)	65 Feet	Red	10 Spools
HTBS-B-075-RD	3/4" (19.05 mm)	2 ± 0.50	-76°F to 500°F (-60°C to 260°C)	3002°F (1650°C)	65 Feet	Red	5 Spools
HTBS-B-100-RD	1" (25.4 mm)	2 ± 0.50	-76°F to 500°F (-60°C to 260°C)	3002°F (1650°C)	65 Feet	Red	3 Spools
HTBS-B-150-RD	1-1/2" (38.1 mm)	3 ± 0.80	-76°F to 500°F (-60°C to 260°C)	3002°F (1650°C)	65 Feet	Red	2 Spools
HTBS-B-200-RD	2" (50.8 mm)	3 ± 0.50	-76°F to 500°F (-60°C to 260°C)	3002°F (1650°C)	65 Feet	Red	1 Spool