

LADDER TIES



Ladder Style Ties

7" / 177.8mm			VIEW ONLINE			
Width	.140"	3.56mm	08470	Natural		1,000 5M
Thickness	.040"	1.02mm	08476	Natural		100 5M
Bundle Diameter (min. — max.)	1/16"—1-3/4"	1.59—44.45mm	08472	Black heat stabilized		1,000 5M
Min. Loop Tensile Strength	40 lbf	18.14kgf / 178N	08478	Black heat stabilized		100 5M

11" / 279.4mm			VIEW ONLINE			
Width	.140"	3.56mm	08471	Natural		1,000 5M
Thickness	.040"	1.02mm	08477	Natural		100 5M
Bundle Diameter (min. — max.)	1/16"—3"	1.59—76.2mm	08473	Black heat stabilized		1,000 5M
Min. Loop Tensile Strength	40 lbf	18.14kgf / 178N	08479	Black heat stabilized		100 5M

Eco Friendly 6/6 Nylon Ladder Ties

- Uses 60% less material when compared to a solid standard tie
- Weighs as much as 60% less when compared to a solid standard tie equivalent
- Save on shipping. The case of Ladder Ties are as much as 17% lighter. The individual bags as much as 5% lighter
- Forty percent of previously used nylon 6/6 material is used in the manufacturing process
- Consistently performs higher than the 40lb. tensile strength specification

When compared to its standard equivalent, the Ladder Tie is both friendly to our environment and cost effective.

The Ladder Tie has been accepted in the Automotive, Electronics and Industrial industries.