

Natural Cable Ties



Kable Kontrol® Clear Natural Nylon Cable Ties are the ideal high-quality, durable, and cost-effective option for all indoor zip tie applications. These cable ties are not actually transparent or see-through. Instead, they are natural nylon. These natural cable ties are specifically manufactured to be used for indoor or in-wall cable bundling due to the fact that they meet industry standards for low smoke production. Our natural zip ties are available from 4" to 60" in length with numerous tensile breaking strengths.

- **Material: Nylon 6/6**
- **UL Listed, File No. E530766 Positioning Device 33AS**
- **UL Standard UL 62275 TYPE 21 or 21S**
- **AH-2 Plenum Rating**
- **Operating temperature range -40°F to +185° F**
- **Humidity absorption: 2,7%-2,8% (23°C -50% R.H.)**
- **Resistance to bases, oils, greases, oil derivatives, and chloride solvents**

SKU	Length	Width	Strength	Pack Quantity
CT204	4"	2.5mm	18 lbs.	100
CT202	4"	2.5mm	18 lbs.	1000
CT505-M+	5.5"	2.5mm	18 lbs.	1000
CT507-NT+	5.5"	3.5mm	40 lbs.	1000
CT295	8"	2.5mm	18 lbs.	1000
CT241+	8"	3.5mm	40 lbs.	1000
CT261+	8"	4.8mm	50 lbs.	100
CT207+	8"	4.8mm	50 lbs.	1000
CT269+	8"	7.6mm	120 lbs.	100
CT108+	9"	12.7mm	250 lbs.	100
CT262+	11"	4.8mm	50 lbs.	100

Natural Cable Ties [cont.]

SKU	Length	Width	Strength	Pack Quantity
CT220+	11"	4.8mm	50 lbs.	1000
CT270+	11"	7.6mm	120 lbs.	100
CT265+	14"	4.8mm	50 lbs.	100
CT256+	14"	4.8mm	50 lbs.	1000
CT271+	14"	7.6mm	120 lbs.	100
CT15NAT+	15"	12.7mm	250 lbs.	100
CT17-175N+	17"	9mm	175 lbs.	100
CT7108+	18"	7.6mm	120 lbs.	100
CT19NAT+	19"	12.7mm	250 lbs.	100
CT110+	22"	12.7mm	250 lbs.	100
CT-24-NU-100PK+	24"	9mm	175 lbs.	100
CT272+	28"	9mm	175 lbs.	100
CT273+	32"	9mm	175 lbs.	50
CT289+	36"	4.8mm	50 lbs.	100
CT297-50+	36"	9mm	175 lbs.	50
CT40NAT-50+	40"	12.7mm	250 lbs.	50
CT294+	48"	9mm	175 lbs.	50
CT298+	60"	9mm	175 lbs.	50

SKU's followed by a plus (+) support custom marking personalization.

SKU's followed by an asterisk (*) currently do not possess a UL listing.

UV Resistant Black Cable Ties



Kable Kontrol® Black Nylon Cable Ties provide a reliable and cost-effective solution for cable management across various applications. Crafted from premium nylon 6/6 with UV stabilization, they offer exceptional strength, weather resistance, and durability for indoor and outdoor use. Available in sizes ranging from 4 to 60 inches, these zip ties are designed for versatility, securing cables in settings from homes to industrial environments. Their self-locking mechanism ensures a secure grip and easy installation, while competitive pricing guarantees value without compromising quality. With a wide range of tensile strengths, sizes, and certifications, Kable Kontrol UV Resistant Cable Ties deliver peace of mind and superior performance in any setting.

- **Material:** Nylon 6/6
- **Operating temperature range** -40°F to +185° F
- **Humidity absorption:** 2,7%-2,8% (23°C -50% R.H.)
- **Resistance to bases, oils, greases, oil derivatives, and chloride solvents**

- **UL Listed, File No. E530766 Positioning Device 33AS**
- **UL Standard UL 62275 TYPE 21 or 21S**
- **AH-2 Plenum Rating**
- **UV Rated**

SKU	Length	Width	Strength	Pack Quantity
CT242	4"	2.5mm	18 lbs.	100
CT208	4"	2.5mm	18 lbs.	1000
CT506-M	5.5"	2.5mm	18 lbs.	1000
CT507-BK+	5.5"	3.5mm	40 lbs.	1000
CT259+	8"	2.5mm	18 lbs.	1000
CT243+	8"	3.5mm	40 lbs.	1000
CT266+	8"	4.8mm	50 lbs.	100
CT209+	8"	4.8mm	50 lbs.	1000
CT-08-75-100-BK+	8"	4.8mm	75 lbs.	100
CT278+	8"	7.9mm	120 lbs.	100

SKU's followed by a plus (+) support custom marking personalization.

UV Resistant Black Cable Ties [cont.]

SKU	Length	Width	Strength	Pack Quantity
CT102+	9"	12.7mm	250 lbs.	100
CT267+	11"	4.8mm	50 lbs.	100
CT221+	11"	4.8mm	50 lbs.	1000
CT277+	11"	7.6mm	120 lbs.	100
CT-12-75-100-BK	12"	5.8mm	75 lbs.	100
CT268+	14"	4.8mm	50 lbs.	100
CT257+	14"	4.8mm	50 lbs.	1000
CTUV-14-75-100-BK*+	14"	4.8mm	75 lbs.	100
CT274+	14"	7.6mm	120 lbs.	100
CT15BK+	15"	12.7mm	250 lbs.	100
CTUV-18-50-100-BK*+	18"	4.8mm	50 lbs.	100
CT7109+	18"	7.6mm	120 lbs.	100
CT-18-175-BK+	18"	9mm	175 lbs.	100
CT19BK+	19"	12.7mm	250 lbs.	100
CT-20-300-100-BK	20"	12.4mm	300 lbs.	100
CT104+	22"	12.7mm	250 lbs.	100
CT-24-BK-100PK+	24"	9mm	175 lbs.	100
CT276+	28"	9mm	175 lbs.	100
CT275+	32"	9mm	175 lbs.	50
CT299+	36"	4.8mm	50 lbs.	100
CT297HV-50+	36"	9mm	175 lbs.	50
CT40BK-50+	40"	12.7mm	250 lbs.	50
CT293+	48"	9mm	175 lbs.	50
CT298B+	60"	9mm	175 lbs.	50

SKU's followed by a plus (+) support custom marking personalization.

SKU's followed by an asterisk (*) currently do not possess a UL listing.