

Kable Kontrol® Heat Resistant Braided Fiberglass Cable Sleeve

Technical Specifications

Part Number	Inside Diameter	Wall Thickness (mm)	Operating Temperature	Electrical Rating	Flame Rating	Length	Color	Case Quantity
HTBS-A-025-BK	1/4" (6.35 mm)	0.39 ± 0.10	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	50' 328'	Black	8 Spools
HTBS-A-037-BK	3/8" (9.53 mm)	0.47 ± 0.15	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	50' 164'	Black	12 Spools
HTBS-A-050-BK	1/2" (12.7 mm)	0.51 ± 0.15	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	50' 164'	Black	8 Spools
HTBS-A-062-BK	5/8" (15.87 mm)	0.51 ± 0.16	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	50' 164'	Black	8 Spools
HTBS-A-075-BK	3/4" (19.05 mm)	0.61 ± 0.17	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	50' 164'	Black	6 Spools
HTBS-A-087-BK	7/8" (22.23 mm)	0.61 ± 0.20	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	50' 164'	Black	6 Spools
HTBS-A-100-BK	1" (25.4 mm)	0.61 ± 0.20	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	25' 164'	Black	6 Spools
HTBS-A-150-BK	1-1/2" (38.0 mm)	0.76 ± 0.15	-40°F to +662°F (-40°C to +350°C)	600V	VW-1	25' 82'	Black	4 Spools

