

Kable Kontrol® Non-Fray Expandable Braided Cable Sleeving

Technical Specifications

Part Number	Inside Diameter	Operating Temperature	Expandable Range	Material	Flame Rating	Length	Color
KKNF-012-BK**	1/8 (3mm)	-40°F to 257°F (-40°C to +125°C)	0.04" - 0.24" (1 - 6mm)	Polyester	UL94 V0	100' 1000'	Black
KKNF-025-BK**	1/4 (6±2mm)	-40°F to 257°F (-40°C to +125°C)	0.12" - 0.35" (3 - 9mm)	Polyester	UL94 V0	100' 1000'	Black
KKNF-037-BK**	3/8 (10±3mm)	-40°F to 257°F (-40°C to +125°C)	0.28" - 0.67" (7 - 17mm)	Polyester	UL94 V0	100' 500'	Black
KKNF-050-BK**	1/2 (12±3)	-40°F to 257°F (-40°C to +125°C)	0.31" - 0.79" (8 - 20mm)	Polyester	UL94 V0	100' 500'	Black
KKNF-075-BK**	3/4 (19±3)	-40°F to 257°F (-40°C to +125°C)	0.55" - 1.18" (14 - 30mm)	Polyester	UL94 V0	50' 250'	Black
KKNF-100-BK**	1 (25±5)	-40°F to 257°F (-40°C to +125°C)	0.71" - 1.3" (18 - 33mm)	Polyester	UL94 V0	50' 250'	Black
KKNF-150-BK**	1-1/2 (38±5)	-40°F to 257°F (-40°C to +125°C)	1.18" - 2.36" (30 - 60mm)	Polyester	UL94 V0	50' 200'	Black