


Locking Tie Cable Ties – Weather Resistant Nylon 612

- Excellent UV resistance providing up to a 20-year life expectancy
- For high moisture, corrosive (zinc chloride and dilute acids), and low temperature indoor or outdoor applications
- Cable tie of choice for making attachments to galvanized surfaces
- One-piece construction for consistent performance and reliability
- Among the lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



Part Number	Length In. (mm)	Width In. (mm)	Thickness In. (mm)	Max Bundle Diameter In. (mm)	Minimum Loop Tensile Strength Lbs. (N)	Recommended Installation Tool	Pkg. Qty.*	Bulk Ctn. Qty.
Miniature Cross Section								
PLT1M-M6120	3.9 (99)	0.098 (2.5)	0.043 (1.1)	0.87 (22)	20 (89)	GTS-E, GS2B-E, PTS, PPTS, STS2	1,000	50,000
PLT1M-C6120							100	1,000
Intermediate Cross Section								
PLT1.5I-M6120	5.6 (142)	0.142 (3.6)	0.045 (1.1)	1.38 (35)	25 (111)	GTS-E, GS2B-E, PTS, PPTS, STS2	1,000	25,000
PLT1.5I-C6120							100	1,000
Standard Cross Section								
PLT2S-M6120	7.4 (188)	0.19 (4.8)	0.047 (1.2)	1.88 (48)	50 (222)	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	1,000	10,000
PLT2S-C6120							100	1,000
PLT2.5S-M6120	9.8 (249)		2.5 (64)	1,000			10,000	
PLT2.5S-C6120				100			1,000	
PLT3S-M6120	11.5 (292)		0.052 (1.3)	3.0 (76)			1,000	10,000
PLT3S-C6120							100	1,000
PLT4S-M6120	14.5 (368)		4.0 (102)	1,000			5,000	
PLT4S-C6120				100			1,000	
Light-Heavy Cross Section								
PLT4H-TL6120	14.5 (368)	0.3 (7.6)	0.075 (1.9)	4.0 (102)	120 (534)	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	250	1,000
PLT7LH-C6120	24.7 (627)			7.0 (178)			100	2,000
PLT8LH-C6120	27.6 (701)			8.0 (203)				

*Order number of pieces required, in multiples of Packages Quantity