



Most Advanced Hose Protection Solution

DURA FLEX PROFESSIONAL (DPN) provides tough hose protection in two ways. First, per the ISO 6945 spec, DPN's unique 80 mil thick tubular weave design will withstand up to 13,000 abrasion cycles without wearing through the fabric at any location.

Additionally, the exceptionally smooth inner wall provides easy installation and minimizes any internal abrasion problems. The tightly woven nylon construction is extremely flexible and resists chemical and ultraviolet degradation. Dura-Flex Professional cuts with a scissor, and installs quickly and easily. DPN is perfect for industrial and construction applications where adequate protection is needed.

- **13,000 Cycles***
- **Heavy Duty, 80 Mil Wall Thickness**
- **ISO 6945 Certified**
- **Professional Grade Construction**
- **Smooth Inner Wall Prevents Internal Abrasion Damage**
- **Nylon Construction Resists UV, Salt, Chemicals, Vermin, and Rot**



When every second counts, Dura Flex Pro is your thickest protection for the longest wear.



Techflex® Dura Flex products add increased safety in confined spaces such as mines.



Whatever your hose or application, DPN will provide an extra level of protection from cuts, abrasion, and UV damage.

Nominal Size	Part #	Wall Thickness	Standard Spool Put-Ups		Available Colors	Lbs/100'
			Bulk Spool	Shop Spool		
0.75"	DPN0.75BK	.08"	100'	50'	Black (BK)	4.43
0.93"	DPN0.93BK	.08"	100'	50'	Black (BK)	5.51
1.13"	DPN1.13BK	.08"	100'	50'	Black (BK)	7.15
1.25"	DPN1.25BK	.08"	100'	50'	Black (BK)	7.44
1.35"	DPN1.35BK	.08"	100'	50'	Black (BK)	8.02
1.43"	DPN1.43BK	.08"	100'	50'	Black (BK)	8.32
1.63"	DPN1.63BK	.08"	100'	50'	Black (BK)	9.53
1.81"	DPN1.81BK	.08"	100'	50'	Black (BK)	10.71
2.19"	DPN2.19BK	.08"	100'	50'	Black (BK)	12.31
2.38"	DPN2.38BK	.08"	100'	50'	Black (BK)	13.70
2.63"	DPN2.63BK	.08"	100'	50'	Black (BK)	14.83
2.88"	DPN2.88BK	.08"	100'	50'	Black (BK)	17.30
3.13"	DPN3.13BK	.08"	50'	25'	Black (BK)	18.04
3.38"	DPN3.38BK	.08"	50'	25'	Black (BK)	20.11
3.63"	DPN3.63BK	.08"	50'	25'	Black (BK)	21.60
4.00"	DPN4.00BK	.08"	50'	25'	Black (BK)	23.52



MSHA ISO 6945

Abrasion Resistance						
630	950	2,500	3,500	4,400	8,500	*13,000
HIGH			EXTREMELY HIGH			